



INSTRUMENT DATA SHEET

DOCUMENT NO. 100-0109 Rev. 11

**SAGE PRIME
THERMAL MASS FLOW
METER**

GAS MASS FLOW

**SAGE SRP SPECIFICATIONS
REMOTE STYLE PRIME
INSERTION MASS FLOW METER**

GENERAL INFORMATION

STYLE:	Remote Insertion Mass Flow Meter
SENSOR:	Two reference grade platinum RTD clad in 316SS sheath
MATERIAL:	Wetted metal components: 316SS
POWER:	24VDC Standard (12VDC or 115/230VAC optional)
POWER DISSIPATION:	<2.5 W
ELECTRONICS:	Remote-Style Microprocessor based (Hybrid-Digital)
PROBE ENCLOSURE:	Junction Box is Explosion Proof, Class I, Div 2, Groups B, C, D (no electronics)
TRANSMITTER ENCLOSURE:	Remote mount, NEMA 4 enclosure
DISPLAY:	High contrast photo-emissive OLED graphical display (Flow Rate, Totalizer, Temperature)
TURNDOWN:	100 to 1
RESOLUTION:	1000 to 1
LOW END SENSITIVITY:	5 SFPM
FIELD CALIBRATION CHECK:	Yes - Digital system allows raw signal validation (milli-watts)
COMMUNICATIONS:	Modbus® compliant RS485 RTU or optional HART® communications
APPROVALS:	CSA C22.2 (24 VDC); ULI604, Class I, Div 2, Groups B, C, D T4 (24VDC); CE (AC Power or 24VDC)
FIELD RECONFIGURABLE:	Sage ADDRESSER required
FLOW ACCURACY:	+/- 0.5% of Full Scale +/- 1% of reading (Enhanced accuracy optionally available with limited turn-down)
FLOW REPEATABILITY:	0.2%
RESPONSE TIME:	1 second time constant
GAS TEMPERATURE RANGE:	Standard -40° to 200°F (93°C), Optional to 300°F (149°C) and 450°F (232°C)
GAS PRESSURE:	500 PSIG (If higher pressure needed, contact Sage)
FLOW OUTPUT:	4 to 20 mA for Rate
TOTALIZER:	24VDC pulse for Totalized value
TEMPERATURE OUTPUT:	Through Modbus® only
AMBIENT TEMPERATURE:	-40°F to 150°F (66°C)
PROBE STYLE / LENGTH:	1/2" OD Probe (3/4" optional) Lengths 6" to 36"
RELAYS:	N/A
CABLE LENGTH:	25' Standard (max length 1000')
FLOW CONDITIONING:	Captive Flow Conditioners available upon request with meter purchase
TRANSMITTER ENCL DEPTH:	DC: 4.35" ; AC: 5.35"

Make the Wise Choice. Choose Sage Flow Meters.

